

SPECIFICATIONS TO QUOTE THE MOULD FOR CONCRETE AND GRASS MODI' CE 080

To lay a paved surface with the Mould for Concrete and Grass MODI' :

- A) Supply and fit of continuous 200 ÷ 400 gr/m² T.N.T. thread (optional) = €/m²...
- B) Supply and fit of ... cm foundation layer, consisting of stabilized, well-levelled, rolled and compacted crushed stone of variable sizes. = €/m²...
- C) Supply and fit of about 3 cm sand layer. = €/m²...
- D) Supply and fit of the Mould for Concrete and Grass MODI' made of UV-resistant recyclable HDPE; height 8 cm, surface area cm 60 x 60. The Mould MODI' has 27 formers per m², the distance between the axles is cm 20 x 20. The formers have the shape of four-leaf lover and they are sheared on the superior part. The support surface of the Mould is 0,43 m²/m². The surface with grass is the 32 %. = €/m² ...
- E) Supply and fit of wire mesh Ø mm... with mesh of cm 20 x 20 with overlap:
kg/mq ... x €/kg ... = €/m² ...
- F) Supply and lay of the concrete Rck≥250 kg/cm². Considering to prepare adequate joints in the two directions of laying each 4 ÷ 4,5 m. To level top of formers of the Mould MODI' the consumption of concrete is 0,044 m³/m². = €/m²...
- G) Fill the empty formers obtained shearing the top of four-leaf lover formers with organic soil. The soil consumption is 0,035 m³/m². = €/m²...
- H) Sowing of the lawn. = €/m²...