

SPECIFICATIONS FOR QUOTE GARDEN GRID MODÌ

To lay a paved surface for a new lawn, using a MODÌ flooring grid:

- A) Supply and fit of continuous 200 ÷ 400 gr/m² T.N.T. thread (optional) = €/m².....
- B) Supply and fit of 5 ÷ 50 cm foundation layer, consisting of stabilised, well-levelled, rolled and compacted crushed stone = €/m².....
- C) Supply and fit of 3 cm sand layer = €/m².....
- D) Supply and fit of the MODÌ UV-resistant recyclable HDPE Flooring Grid, height: 4 cm, surface area: 58x58 cm. This Grid, supplied with ready prepared communicating 'buttonholes' and drainage system, of a maximum size of 27x15 mm, has transversal and longitudinal light and aerobic function. It has small water tanks in each cell, and which are able to retain a quantity of water equal to 1.5 l/m². The top side has a rib network, and the bottom side has an intercommunicating rib network, designed to hold the underlying sand, thus guaranteeing extreme stability. It is made up of a variety of differently shaped cells (circles, squares, rhombi and trapeziums) and of "λ" shaped ribs, giving a strong frame with a good level of elasticity, certified for up to 187 tons/m². The Grid has a unique bi-directional attachment system (it can be positioned either way around), with "Ω" and "C" shaped links, to simplify lay, and a non-slip surface with rounded studs. = €/m².....
- E) Supply and fit of Ø 62 mm MODÌ specific markers, in colour, made from first class acetyl resin, to border the parking area
pc/m² x €/pc = €/m².....
- F) Fill of MODÌ Flooring Grid cells of the Garden Grid with organic soil, peat and sand to just below the edges. = €/m².....
- G) Sowing of lawn = €/m².....