

## SPECIFICATIONS FOR QUOTE ROOF GARDEN MODÌ

Roof garden created as follows:

- Supply and fit of 4 mm thick anti root sheet €/m<sup>2</sup> ...
- Supply and fit of **MODÌ** drainage elements, made from recycled plastic, resistant to chemical and organic substances, height: ..... cm (5 or 9), laid onto self-locking waterproofing. Element size: 58x58 cm.  
**MODÌ** elements have 39 circular-base, rounded tanks for each m<sup>2</sup>, that are pre-prepared for a staggered layout, and with a water reserve system of .....l/m<sup>2</sup> (14 or 18). The total surface area for the support of the water tank feet is .....cm<sup>2</sup>/m<sup>2</sup> (1240 or 609), with a resistance to compression greater than 10,000 kg/m<sup>2</sup>.  
**MODÌ** elements are supplied pre-prepared with 192 holes per m<sup>2</sup>, each with a diameter of 8 mm, to avoid the passage of roots, and have an exceptional drainage system. Fit includes any eventual cutting.  
**MODÌ** size: ..... cm (5 or 9) €/m<sup>2</sup> ...
- Supply and fit of volcanic lapillus or pumice stone, granulated to 10 -12 mm to fill tanks €/m<sup>2</sup> ...
- Supply and fit of continuous thread 200 g/m<sup>2</sup> polypropylene or polyester non wovens, as a separating layer between the **MODÌ** elements and the soil €/m<sup>2</sup> ...
- Supply and fit of soil, to a thickness of .....cm (15 - 50), suitable for intensive or extensive type roof gardens. €/m<sup>2</sup> ...

N.B.: **MODÌ** Garden Grid must be applied on top of **MODÌ** drainage elements, in order to avoid substrate slippage. Special wedges must be used to hold it in place.

**Claudioforesi srl – Via Fosso 2/4 – 60027 S.Biagio – Osimo (AN)**

**Tel. 071 7109309 – 071 7202204 Fax 071 7108180**

**e-mail: [info@claudioforesi.it](mailto:info@claudioforesi.it) - [www.claudioforesi.it](http://www.claudioforesi.it)**